

| <b>Model</b>                 | <b>VICTOR 5150</b>                            | <b>VICTOR 5200</b> | <b>VICTOR 5</b> |
|------------------------------|---|--------------------|-----------------|
| <b>Measurement range</b>     | 150mm/6"                                      | 200mm/8"           | 300mm/12"       |
| <b>Accuracy</b>              | 0.01mm/0.0005"                                | 0.01mm/0.0005"     | 0.01mm/0.0005"  |
| <b>L</b>                     | 235mm   | 287mm              | 390mm           |
| <b>A</b>                     | 40mm  | 50mm               | 60mm            |
| <b>B</b>                     | 21mm  | 24mm               | 27mm            |
| <b>C</b>                     | 16mm  | 16mm               | 16mm            |
| <b>D</b>                     | 3.5mm   | 3.5mm              | 4.0mm           |
| <b>Repeatability</b>         | 0.01mm/0.0005"                                |                    |                 |
| <b>Measurement speed</b>     | 3 m/s   |                    |                 |
| <b>Operating temperature</b> | 0°C~40°C                                      |                    |                 |
| <b>Power</b>                 | SR44(silver oxide cell) 1.5V 1 battery        |                    |                 |
| <b>Average battery life</b>  | The warranty is above 1 year under normal use |                    |                 |