



Item No: WX1010N

1-Channel Soldering Station, 200 W

KEY FEATURES

- 🔒 High Powered Digital Soldering Stations
- Capacitive glass touch screen is chemical and temperature resistant
- Turn and click wheel with enter key and finger guide is intuitive to use
- Multi-language menu , ready for automation using RS232 Serial I/O commands
- Large graphic LCD display can be viewed from all angles
- Acts as a benchtop controller for the WHP 1000 / WHP 3000 hot plates
- 🔒 Acts as a benchtop controller for the Zero Smog 4V / 6V Filtration units
- Multi-purpose USB port for parameter configuration and DATA LOGGING
- Compatible with all WX series soldering pencils

TECHNICAL DATA

Dimensions L x W x H	6.6 x 5.9 x 5.1 in
Equipotential Bonding Socket	Via 3.5mm Pawl Socket on Back of Device
ESD Safe	Yes
Interface	1x USB, 2x RS232, 1x Switching Output
Number of Channels	1
Power	200 W
Temperature Accuracy °C	±9°C
Temperature Accuracy °F	± 17 °F
Temperature Range (Depends on Tool)	199 - 998°F
Temperature Range °C	93 - 537 °C
Temperature Range °F	199 - 998 °F
Temperature Stability °C	±2 °C
Temperature Stability °F	±4 °F
Tip Type	WX WXMT-MS XTB
UPC	037103304773
USB	USB interface of firmware updates, parameterization and monitoring USB interface supports all standard USB flash drive types